


	E-XLR8 (G) (BL)							
Frame sizes	50-54-57-60cm							
Frame description	Completely hand-built Super Smooth TIG-welded frame. Tubes manufactured in double- hardened and double butted 6061 aluminium. Down tube with integrated shifter and brake cables. Equipped with: integrated Bosch engine, headset and basements for all accessories.							
Front fork	Koga Pinza DB - Full Carbon							
Headset	Industrial bearing - Integrated in frame							
Colour	Matt Black							
Handlebar	Koga Oversized SportTouring alloy							
Stem	Koga - Adjustable - A-head							
Grips	rmanns Adrenalin Ergo - Triple Density - Lockable							
Shift lever (r)	Shimano SLX							
Disc-/Hydraulic brake set (f)	Magura MTE							
Disc-/Hydraulic brake set (r)	Magura MTE							
Shifter cable	Stainless steel inner cable -Flexible outer cable with teflon tube for light shifting							
Rotor front	Tektro airflow design ø 160 mm							
Rotor rear	Tektro airflow design ø 160 mm							
Chain	KMC X10e							
Front hub	Shimano - Double contact sealing for low maintenance and increased service life							
Rear hub	Shimano - Double contact sealing for low maintenance and increased service life							
Tires	Vredestein Perfect-E 40mm - Sportex Protection Layer® - Side reflection							
Tube	Schwalbe							
Rims	Mach 1 560							
Rim tape	Hermanns innertube protective							
Spokes	Mach 1							
Saddle	Коаа							
Seat post	Koga alloy - Safety Clamp construction							
Seat clamp	Koga alloy Salety Clarip Construction Koga - Alloy							
Crank set	Miranda 20T							
Bottom bracket								
Pedals	Bosch BracketEngine 500W, 60Nm, 36V (System: Performance Line)							
	Koga Sole-Mate - Concaved anti slip layer - Industrial bearing - ED coated body							
Cassette	Shimano HG-10 speed - Hyperglide for quick and smooth shifting - Sprockets: 11-13-15-17-19-21-24-28-32-36T							
Rear derailleur	Shimano SLX shadow - Low profile design for more aggressive riding							
Pump	Koga Telescopic with alloy barrel - Schrader and Presta Fit - High Pressure/ Big Volume switch - Ergonomic hinge grip							
Bell	Widek Compact							
Chain guard	Koga DeFenz							
Mudguard (f)	Koga							
Mudguard (r)	Koga							
Headlight	B&M Lumotec IQ Cyo - IQ Long life LED technology 40 Lux - Daylight function - KBA approved							
Rear light	Busch&Müller Toplight Line - Long life LED Linetec technique: Improved distance estimation to Cyclist - KBA approved - Seperate brake/license plate light							
Rear carrier	Koga LoDo -Alloy hollow tubing max 25 kg - Durable finish							
Rubber strap	Springclamp							
Kickstand	Pletscher Comp - Superb stability - Powdercoated durable finish							
Ring lock	Trelock RS 450 - ART ** Approved							
Display	Bosch Intuvia							
Battery	Bosch Li-lon 400Wh (36V*11Ah) Removable from DownTube							
Accessories	HandlebarControl Unit							
Weight	21,8							
Gears	10							



Gents

Size	1/1	C/S	Wheelbase	BB-Drop	Rake	H/T Angle	S/T Angle	Trail	H/T	Reach	Stack
50	575	467	1084	55	45	70,5	72,0	75	125	384	590
54	590	467	1077	55	45	71,5	71,0	68	140	381	608
57	605	467	1092	55	45	71,5	71,0	68	160	389	627
60	620	467	1107	55	45	71,5	71,0	68	185	396	651

© 2015 KOGA reserves the right to make changes to specifications and/or prices without further notice. Although this brochure has been compiled with the utmost care, no liability can be taken for any remaining errors of any type. Reproduction of this publication is prohibited unless expressly permitted in writing by KOGA.