

	Prominence (G) (PR)	Prominence (L) (PRL)
Frame sizes	54-57-60-63-66cm	47-50-53-56-59cm
Frame description	Completely hand-built Super Smooth TIG-welded frame. Tubes manufactured in triple-hardened and triple butted 7005 aluminium. Down tube with integrated shifter cables, Top tube with integrated brake cable. Equipped with: Tapered headtube with integrated 1 1/8"/1 1/4" headset, rear carrier, replaceable rear derailleur hanger and basements for all accessories.	Completely hand-built Super Smooth TIG-welded low step-through frame. Tubes manufactured in triple-hardened and triple butted 7005 aluminium. Down tube with integrated shifter cables, Top tube with integrated brake cable. Equipped with: Tapered headtube with integrated 1 1/8"/1 1/4" headset, rear carrier, replaceable rear derailleur hanger and basements for all accessories.
Front fork	Koga Feather Lightweight - Ball bearing guided suspension fork - Travel 35 mm	Koga Feather Lightweight - Ball bearing guided suspension fork - Travel 35 mm
Headset	Industrial bearing - Integrated in frame	Industrial bearing - Integrated in frame
Colour	Royal Blue/Titan	Royal Blue/Titan
BrakePowerControl	Koga BrakePowerControl for a well dosed braking performance	Koga BrakePowerControl for a well dosed braking performance
Handlebar	Koga Touring alloy	Koga Touring alloy
Stem	Koga Justera - Adjustable A-head	Koga Justera - Adjustable A-head
Grips	Koga grips	Koga grips
Brake (front)	Shimano Deore LX V-rimbrake	Shimano Deore LX V-rimbrake
Brake (rear)	Shimano Deore LX V-rimbrake	Shimano Deore LX V-rimbrake
Shift/Brake lever (r)	Shimano LX Rapidfire Plus - Two Way release - Optical gear display	Shimano LX Rapidfire Plus - Two Way release - Optical gear display
Shift/Brake lever (l)	Shimano LX Rapidfire Plus - Two Way release - Optical gear display	Shimano LX Rapidfire Plus - Two Way release - Optical gear display
Brake cable	Stainless steel inner cable -Flexible outer cable with PTFE tube for light braking	Stainless steel inner cable -Flexible outer cable with PTFE tube for light braking
Shifter cable	Stainless steel inner cable -Flexible outer cable with PTFE tube for light shifting	Stainless steel inner cable -Flexible outer cable with PTFE tube for light shifting
Chain	Shimano Deore LX Hyperglide for smooth shifting and riding	Shimano Deore LX Hyperglide for smooth shifting and riding
Front hub	Shimano LX 6V/3,0W - Lightweight sporthub - Low rotating friction - Quick Release	Shimano LX 6V/3,0W - Lightweight sporthub - Low rotating friction - Quick Release
Rear hub	Shimano Deore LX - Double contact sealing for low maintenance and increased service life	Shimano Deore LX - Double contact sealing for low maintenance and increased service life
Tires	Schwalbe marathon Supreme 37 mm - HD Speed Guard: Vectran puncture protection - RoadStar Triple Compound: low rolling resistance + Supreme grip - Side reflection - Foldable	Schwalbe marathon Supreme 37 mm - HD Speed Guard: Vectran puncture protection - RoadStar Triple Compound: low rolling resistance + Supreme grip - Side reflection - Foldable
Tube	Koga	Koga
Rims	Koga KM19-622 Xlite alloy - Double wall and double eyeletted 36 holes - Durable finished	Koga KM19-622 Xlite alloy - Double wall and double eyeletted 36 holes - Durable finished
Rim tape	Hermanns innertube protective	Hermanns innertube protective
Spokes	Sapim stainless - Cold forged reinforced	Sapim stainless - Cold forged reinforced
Saddle	Koga Komforza Genuine Leather sides	Koga Komforza Genuine Leather sides
Seat post	Koga alloy - Shock absorbing - Safety Clamp construction - Travel 30mm	Koga alloy - Shock absorbing - Safety Clamp construction - Travel 30mm
Seat clamp	Koga - Alloy	Koga - Alloy
Crank set	Shimano Deore LX Hollowtech II - Lightweight - Hyperdrive chainrings for smooth and precise shifting: 44x32x22T	Shimano Deore LX Hollowtech II - Lightweight - Hyperdrive chainrings for smooth and precise shifting: 44x32x22T
Pedals	Koga Sole-Mate - Concaved anti slip layer - Industrial bearing - ED coated body	Koga Sole-Mate - Concaved anti slip layer - Industrial bearing - ED coated body
Cassette	Shimano 105 10 speed - Hyperglide for quick and smooth shifting - Sprockets: 11-12-13-14-15-17-19-21-24-28T	Shimano 105 10 speed - Hyperglide for quick and smooth shifting - Sprockets: 11-12-13-14-15-17-19-21-24-28T
Rear derailleur	Shimano Deore LX	Shimano Deore LX
Front derailleur	Shimano deore LX	Shimano Deore LX
Derailleur guard	Koga Q-guard: combined Quick Release and rear derailleur protection	Koga Q-guard: combined Quick Release and rear derailleur protection
Pump	Koga Telescopic with alloy barrel - Schrader and Presta Fit - High Pressure/ Big Volume switch - Ergonomic hinge grip	Koga Telescopic with alloy barrel - Schrader and Presta Fit - High Pressure/ Big Volume switch - Ergonomic hinge grip
Bell	Widek Compact	Widek Compact
Chain guard	Koga Suomi Comfort	Koga Suomi Comfort
Mudguard (f)	Koga	Koga
Mudguard (r)	Koga	Koga
Coat guards	Koga Espejitos Lightweight	Koga Espejitos Lightweight
Headlight	Koga Rayo Senso Crown Connect - New IQ-LED technology 35 Lux - Integrated reflector - Standlight & Daylight function - KBA approved	Koga Rayo Senso Crown Connect - New IQ-LED technology 35 Lux - Integrated reflector - Standlight & Daylight function - KBA approved
Rear light	Busch&Müller Koga Luminance - Multiangle Long life 5*LED Linetec technique - Standlight function - KBA approved	Busch&Müller Koga Luminance - Multiangle Long life 5*LED Linetec technique - Standlight function - KBA approved
Dynamo	Hub	Hub
Rear carrier	Racktime frame integrated - Alloy hollow tubing max 25 kg - Durable black finish	Racktime frame integrated - Alloy hollow tubing max 25 kg - Durable black finish
Rubber strap	Koga TriFlex	Koga TriFlex
Kickstand	Atran Velo Move - Superb stability - Powdercoated durable finish	Atran Velo Move - Superb stability - Powdercoated durable finish
Ring lock	AXA Defender RL - ART ** Approved - Folding key	AXA Defender RL - ART ** Approved - Folding key
Weight	15.5	15.9
Gears	30	30

Gents

Size	T/T	C/S	Wheelbase	BB-Drop	Rake	H/T Angle	S/T Angle	Trail	H/T
54	572	457	1082	55	45	69,5	72,0	85	120
57	584	457	1072	55	45	70,5	71,0	79	140
60	596	457	1084	55	45	70,5	71,0	79	165
63	608	457	1084	55	45	70,5	70,0	79	195
66	620	457	1095	55	45	70,5	70,0	79	230

Ladies

Size	T/T	C/S	Wheelbase	BB-Drop	Rake	H/T Angle	S/T Angle	Trail	H/T
47	562	457	1067	69	45	69,5	72,0	85	160
50	569	457	1074	69	45	69,5	72,0	85	170
53	576	457	1082	69	45	69,5	72,0	85	180
56	583	457	1065	69	45	70,5	71,0	79	190
59	590	457	1072	69	45	70,5	71,0	79	200

