

	Venya (G) (VE)	Venya (L) (VEL)
Frame sizes	54-57-60-63-66cm	47-50-53-56-59cm
Frame description	Completely hand-built Super Smooth TIG-welded frame. Tubes manufactured in triple-hardened and triple butted 6061 aluminium. Down tube with integrated shifter cables, Top tube with integrated brake cable. Equipped with: Tapered headtube with integrated 1 1/8"/1 1/4" headset, rear carrier, replaceable rear derailleur hanger and basevents for all accessories.	Completely hand-built Super Smooth TIG-welded low step-through frame. Tubes manufactured in triple-hardened and triple butted 6061 aluminium. Down tube with integrated shifter cables, Top tube with integrated brake cable. Equipped with: Tapered headtube with integrated 1 1/8"/1 1/4" headset, rear carrier, replaceable rear derailleur hanger and basevents for all accessories.
Front fork	KOGA Feather Lightweight - Ball bearing guided suspension fork - Travel 35 mm	KOGA Feather Lightweight - Ball bearing guided suspension fork - Travel 35 mm
Headset	Industrial bearing - Integrated in frame	Industrial bearing - Integrated in frame
Colour	Quartz Grey	Quartz Grey
BrakePowerControl	KOGA BrakePowerControl for a well dosed braking performance	KOGA BrakePowerControl for a well dosed braking performance
Handlebar	KOGA Touring alloy	KOGA Touring alloy
Stem	KOGA Justera - Adjustable A-head	KOGA Justera - Adjustable A-head
Grips	KOGA Ergonomic	KOGA Ergonomic
Brake (front)	Shimano Deore LX V-rimbrake	Shimano Deore LX V-rimbrake
Brake (rear)	Shimano Deore LX V-rimbrake	Shimano Deore LX V-rimbrake
Shift/Brake lever (r)	Shimano LX Rapidfire Plus - Two Way release - Optical gear display	Shimano LX Rapidfire Plus - Two Way release - Optical gear display
Shift/Brake lever (l)	Shimano LX Rapidfire Plus - Two Way release - Optical gear display	Shimano LX Rapidfire Plus - Two Way release - Optical gear display
Brake cable	Stainless steel inner cable - Flexible outer cable with PTFE tube for light braking	Stainless steel inner cable - Flexible outer cable with PTFE tube for light braking
Shifter cable	Stainless steel inner cable - Flexible outer cable with PTFE tube for light shifting	Stainless steel inner cable - Flexible outer cable with PTFE tube for light shifting
Chain	Shimano Deore LX Hyperglide for smooth shifting and riding	Shimano Deore LX Hyperglide for smooth shifting and riding
Front hub	Shimano LX 6V/3,0W - Lightweight sporthub - Low rotating friction - Quick Release	Shimano LX 6V/3,0W - Lightweight sporthub - Low rotating friction - Quick Release
Rear hub	Shimano Deore LX - Double contact sealing for low maintenance and increased service life	Shimano Deore LX - Double contact sealing for low maintenance and increased service life
Tires	Schwalbe marathon Supreme 37 mm - HD Speed Guard: Vectran puncture protection - RoadStar Triple Compound: low rolling resistance + Supreme grip - Side reflection - Foldable	Schwalbe marathon Supreme 37 mm - HD Speed Guard: Vectran puncture protection - RoadStar Triple Compound: low rolling resistance + Supreme grip - Side reflection - Foldable
Tube	KOGA	KOGA
Rims	Mach 1 550	Mach 1 550
Rim tape	Hermanns innertube protective	Hermanns innertube protective
Spokes	Mach 1	Mach 1
Saddle	KOGA Komforza Genuine Leather sides	KOGA Komforza Genuine Leather sides
Seat post	KOGA alloy - Shock absorbing - Safety Clamp construction - Travel 30mm	KOGA alloy - Shock absorbing - Safety Clamp construction - Travel 30mm
Seat clamp	KOGA - Alloy	KOGA - Alloy
Crank set	Shimano Deore LX Hollowtech II - Lightweight - Hyperdrive chainrings for smooth and precise shifting: 44x32x22T	Shimano Deore LX Hollowtech II - Lightweight - Hyperdrive chainrings for smooth and precise shifting: 44x32x22T
Pedals	KOGA Sole-Mate - Concaved anti slip layer - Industrial bearing - ED coated body	KOGA Sole-Mate - Concaved anti slip layer - Industrial bearing - ED coated body
Cassette	Shimano 105 10 speed - Hyperglide for quick and smooth shifting - Sprockets: 11-12-13-14-15-17-19-21-24-28T	Shimano 105 10 speed - Hyperglide for quick and smooth shifting - Sprockets: 11-12-13-14-15-17-19-21-24-28T
Rear derailleur	Shimano Deore LX	Shimano Deore LX
Front derailleur	Shimano deore LX	Shimano Deore LX
Derailleur guard	KOGA Q-guard: combined Quick Release and rear derailleur protection	KOGA Q-guard: combined Quick Release and rear derailleur protection
Pump	KOGA Telescopic with alloy barrel - Schrader and Presta Fit - High Pressure/ Big Volume switch - Ergonomic hinge grip	KOGA Telescopic with alloy barrel - Schrader and Presta Fit - High Pressure/ Big Volume switch - Ergonomic hinge grip
Bottle		
Bottle holder		
Bell	Widek Compact	Widek Compact
Chain guard	#N/B	#N/B
Mudguard (f)	KOGA	KOGA
Mudguard (r)	KOGA	KOGA
Coat guards	KOGA Espejitos Lightweight	KOGA Espejitos Lightweight
Headlight	KOGA Rayo Senso Crown Connect - New IQ-LED technology 35 Lux - Integrated reflector - Standlight & Daylight function - KBA approved	KOGA Rayo Senso Crown Connect - New IQ-LED technology 35 Lux - Integrated reflector - Standlight & Daylight function - KBA approved
Rear light	B&M Shine Evo LED	B&M Shine Evo LED
Dynamo	Hub	Hub
Rear carrier	KOGA LoDo - Alloy hollow tubing max 25 kg - Durable finish	KOGA LoDo - Alloy hollow tubing max 25 kg - Durable finish
Rubber strap	KOGA TriFlex	KOGA TriFlex
Kickstand	Atran Velo Move - Superb stability - Powdercoated durable finish	Atran Velo Move - Superb stability - Powdercoated durable finish
Ring lock	AXA Victory - ART ** Approved - Anti theft chip - Folding key	AXA Victory - ART ** Approved - Anti theft chip - Folding key
Gears	30	30

Gents

Size	T/T	C/S	Wheelbase	BB-Drop	Rake	H/T Angle	S/T Angle	Trail	H/T	Reach	Stack
54	572	457	1078	55	45	69,5	72,0	85	120	384	579
57	584	457	1069	55	45	70,5	71,0	79	140	377	602
60	596	457	1081	55	45	70,5	71,0	79	165	381	625
63	608	457	1080	55	45	70,5	70,0	79	195	370	654
66	620	457	1092	55	45	70,5	70,0	79	230	370	687

Ladies

Size	T/T	C/S	Wheelbase	BB-Drop	Rake	H/T Angle	S/T Angle	Trail	H/T	Reach	Stack
47	562	457	1064	69	45	69,5	72,0	85	160	357	630
50	569	457	1071	69	45	69,5	72,0	85	170	361	640
53	576	457	1079	69	45	69,5	72,0	85	180	365	649
56	583	457	1061	69	45	70,5	71,0	79	190	355	663
59	590	457	1068	69	45	70,5	71,0	79	200	359	672

